



Marine & Offshore

Certificate number: 19448/C1 BV

File number: MAT 62545-2007

Product code: 90111

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

APPROVAL CERTIFICATE for MATERIALS

This certificate is issued to

ELVAL S.A.
Inofita-Viotia - GREECE

for the type of product

WROUGHT ALUMINIUM ALLOY PRODUCTS

Plates, sheets and strips in grade 5083 and 5086

Requirements:

Bureau Veritas Rules on Materials and Welding for the Classification of Marine Units

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 31 May 2022

For Bureau Veritas Marine & Offshore,

At BV PIRAEUS, on 06 Jul 2017,

Spyros KONTOULIS



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION :

Wrought aluminium alloy products: Plates, sheets and strips.

Aluminium Alloy	Temper condition	Maximum thickness
5083	O/H111/H321	Up to 50mm
	H116	Up to 50mm
5086	O/H111/H321	Up to 12.7mm
	H116	Up to 50mm

Alloys and slabs are made at casting sections. Rolled products made by hot rolling followed or not by cold rolling as applicable.

2. DOCUMENTS AND DRAWINGS :

- Documentation issued by ELVAL S.A. and received the 29/03/2007.
- "Rolled products in aluminium alloys 5083&5086-Manufacturing process" Rev.01 issued by ELVAL S.A. dated 18/05/2017.
- Mechanical properties for products delivered in O/H111 temper condition are to be as per EN485-2:

Aluminium Alloy	Rp0.2 (N/mm ²)	Rm (N/mm ²)	Elongation A%
5083	115 min.	240 min. - 345 max.	15 min.
5086	100 min.	240 min. - 310 max.	16 min.

3. TEST REPORTS :

- Documentation issued by ELVAL S.A. and received the 29 March 2007.
- Photomicrographs issued by ELVAL S.A and received the 23 May 2007.
- Report No.170510-8 dated 05/05/2017 issued by spectrullabs (Pireas).
- Reports issued for coil No.163111701 dated 20/12/2016, issued for coils No.163038001, No.163514901, No.163111601, No.163444401 dated 23/02/2017, for coil No.171616901 dated 26/06/2017, reports "exfoliation corrosion test G66" & "Intergranular corrosion test G67" dated 25/01/2017 issued by ELVAL S.A.

4. APPLICATION / LIMITATION :

As per Bureau Veritas Rules for Classification.

5. PRODUCTION SURVEY REQUIREMENTS :

The wrought aluminium alloy products are to be supplied by ELVAL S.A. in compliance with the type and the requirements described in this certificate. This type of product is within the category IBV of Bureau Veritas Rule Note NR320. BV product certificate is required.

6. MARKING OF PRODUCT :

As per Bureau Veritas Rules for Classification.

7. OTHERS :

This certificate replaces approvals from No.19448/A0 BV to No.19448/C0 BV.

*** END OF CERTIFICATE ***